

EVERUN ER 08, 2022



Kr.: 169.900 ex. mva

Standard utstyr:

- Standard skuffe
- Joystick, mekanisk med gir, høy og lavserie
- Konstant firehjulsdriфт med konverter
- Quick shift av redskap
- Hydraulisk converter
- Euro III standard motor, 34 hk
- Flyt funksjon,
- Ekstra hydraulikk, totalt fire funksjoner
- Kjøre/arbeidslys forover og bakover
- Luksus hytte, tiltbar med ryggekamera og varmeapparat
- Justerbart ratt og sete med setebelte
- Hydrauliske skivebremsere alle hjul og park brems
- Dekk 31/15,5-15
- Lås for løft og styresylinder
- Hydraulisk trykk sjekk system
- Varta batteri type vinter
- Hovedstrøms bryter
- Motorvarmer

Tilbehørsliste:

- Mekaniske pallegafler	Kr.: 6.900,-
- Hydrauliske pallegafler	Kr.: 14.900,-
- Snøskjær, hydraulisk, rett	Kr.: 21.900,-
- Hydraulisk snøskjær med V-blad	Kr.: 26.900,-
- Snøskuffe	Kr.: 7.900,-
- Snøskuffe med hydrauliske vinger, 3m	Kr.: 19.900,-
- 4 i 1 skuffe	Kr.: 12.900,-
- Blandeskuffe (Mixer bucket)	Kr.: 14.900,-
- Sandskuffe	Kr.: 7.900,-
- Gripeskuffe	Kr.: 10.900,-
- Dekk type gress 33/15,5-16,5	Kr.: 7.900,-
- Dekk 12-16,5	Kr.: 8.900,-
- Kjettinger pr par	Kr.: 6.900,-
- Sandspreder front	Kr.: 16.900,-
- Sandspreder bak m/hydraulikk	Kr.: 21.900,-
- Tømmerklo 360 grader	Kr.: 24.900,-
- Feiemaskin	Kr.: 24.900,-
- Feiemaskin med oppsamler	Kr.: 26.900,-
- Feiemaskin med vanntank	Kr.: 29.900,-
- Jordbor 200mm	Kr.: 15.900,-
- Jordbor 300mm	Kr.: 17.900,-
- Rundballeløfter	Kr.: 9.900,-
- Oljefatløfter	Kr.: 9.900,-

Spesifikasjoner

1.0 Engine Details

(1) Model:	ChangchaiZN390Q
(2) Engine Type:	In-line Arrangement, Water-cooled, three-cycle Diesel Engine
(3) Rated Power:	25 KW
(4) Rated Speed:	2500 r/min(rpm)
(5) Fuel Consumption Ration in Standard Working Condition	252 g/kw.H

2.0 Transmission System

(1) Type:	Fixed-spindle Power Shift
(2) Shift Gear Control Oil Pressure	1.0-1.8MPa
(3) Rated Input Speed	2500(rpm)

3.0 Bucket

(1) Bucket Capacity:	0.48 m3
(2) Bucket Width:	1700mm
(3) Bucket Type:	Heavy-duty Bolt on Teeth
(4) Rated Load:	800kg
(5) Net Weight	2700kg

4.0 Overall Dimensions

(1) Overall Length(bucket on ground);	4620mm
(2) Overall Height ;	
(3) Ground to Cab Top:	2540mm
(4) Dumping Height:	2120mm
(5) Min. Base to the Ground	220mm
(6) Overall Width	1500mm

5.0 Operating Specifications

(1) Steering System:	Articulated Frame with Hydraulic Power Steering
(2) Min. Turning Radius:	5200mm
(3) Driving System:	Hydraulic Converter

6.0 Brake System

(1) Service Brake	Four wheel Hydraulic Spread-shoed Brake
(2) Parking Brake	Hand Operated

